

CLAIMS

What is claimed is:

- sub
a1
1. A device comprising:
 - 2 a substrate comprising a voltage switchable dielectric material; and
 - 3 a current carrying formation formed on a plurality of selected sections of a surface
 - 4 of the substrate.
 - 1 2. The device of claim 1, wherein the voltage switchable material comprises a
 - 2 mixture of a binder material, a conductive material, and a cross-linking agent.
 - 1 3. The device of claim 2, wherein the conductive material is dispersed as a powder in
 - 2 the mixture.
 - 1 4. The device of claim 3, wherein the binder material includes a polymer binder, the
 - 2 conductive material includes a metal powder, and the cross-linking agent includes Varox
 - 3 peroxide.
 - 1 5. The device of claim 1, wherein the current carrying formation is electrochemically
 - 2 bonded to the surface of the substrate.
 - sub
B3
 - sub
a2
 - 1 6. The device of claim 1, wherein the surface of the substrate includes one or more
 - 2 vias extending through the substrate, the current carrying formation also being formed on
 - 3 a surface of the substrate defining the vias so that the current carrying formation on the
 - 4 surface of the substrate is electrically contactable from an opposing surface of the
 - 5 ~~substrate.~~

all
cut

SUB
all

1 7. The device of claim 1, wherein the current carrying formation includes a plurality
2 of current carrying elements separated from each other by a plurality of gaps, the plurality
3 of gaps defining selected regions where a non-conductive layer was formed on the surface
4 of the substrate.

1 8. The device of claim 1, further comprising a non-conductive layer on the surface of
2 the substrate, the non-conductive layer having gaps corresponding to the plurality of
3 selected sections where the current carrying formation is formed.

1 9. The device of claim 8, wherein the non-conductive layer comprises a dielectric
2 material that is permanent to the surface of the substrate.

1 10. A device comprising:
2 a substrate comprising a voltage switchable dielectric material, the substrate having
3 a first surface and a second surface opposing the first surface, the substrate
4 further including a vias extending through the substrate;
5 a current carrying formation formed on a plurality of selected sections of the first
6 and second surfaces, and on a surface of the substrate defining the vias to
7 extend an electrical connection from the first surface to the second surface.

1 11. The device of claim 10, wherein the current carrying formation is
2 electrochemically bonded to the first surface, the second surface, and a surface of the
3 substrate defining the vias.

1 12. The device of claim 10, wherein the current carrying formation is formed on a
2 surface of the substrate defining the vias when at least portions of the current carrying
3 formation is being formed on the first and/or the second surface.

1 13. The device of claim 10, wherein the voltage switchable material comprises a
2 mixture of a binder material, a conductive material, and a cross-linking agent.

1 14. The device of claim 13, wherein the conductive material is dispersed as a powder
2 in the mixture.

1 15. A device comprising:
2 a first substrate comprising voltage switchable dielectric material; and
3 a first current carrying formation formed on a plurality of selected sections of a surface of
4 the first substrate;
5 a second substrate comprising voltage switchable dielectric material, the second substrate
6 being adjacent to the first substrate; and
7 a second current carrying formation formed on a plurality of sections of a surface of the
8 second substrate.

1 16. The device of claim 15, wherein the surfaces of the first and second substrates are
2 in electrical contact with each other.

1 17. The device of claim 16, wherein the first substrate includes a vias within the first
2 substrate that accesses the surface of the second substrate, the current carrying formation
3 of the first substrate being formed on the vias to extend electrical contact to the surface of
4 the second substrate from the surface of the first substrate.

sub
a 3

18.

A device comprising:

a substrate comprising a voltage switchable dielectric material; and

a current carrying formation formed on a plurality of selected sections of a surface of the substrate, the current carrying formation being formed on the surface of the substrate by a process that includes contacting the substrate with a current carrying formation precursor while applying a voltage to the substrate that is sufficient to cause the substrate to be conductive.

19.

The device of claim 18, wherein the current carrying formation includes a plurality of current carrying elements separated from each other by a plurality of gaps, the plurality of gaps defining selected regions where a non-conductive layer was formed on the surface of the substrate.

20.

The device of claim 19, wherein the non-conductive layer was formed from a photo-imageable material that was imaged to define the selected sections of the surface of the substrate, and then subsequently removed from the substrate.

21.

The device of claim 20, wherein the non-conductive layer was formed from a photoresist layer that was exposed with a mask, the exposed regions forming the selected regions of the substrate.

22.

The device of claim 20, wherein the current carrying formation includes a plurality of current carrying elements separated by a non-conductive layer, the non-conductive layer being patterned by a process of silk-screening a dielectric layer onto the substrate according to a pattern that defines the selected sections of the surface of the substrate.

1 23. The device of claim 18, wherein the process includes using an electrode to plate
2 the current carrying formation on the selected sections of the substrate.

1 24. The device of claim 23, wherein the process includes applying a pulsed voltage to
2 the electrode while applying the voltage to the substrate that is sufficient to cause the
3 substrate to be conductive in order to plate the current carrying formation on the selected
4 sections of the substrate.

1 25. The device of claim 24, wherein the process includes applying a rectified pulse
2 periodic voltage to the electrode while applying the voltage to the substrate that is
3 sufficient to cause the substrate to be conductive in order to plate the current carrying
4 formation on the selected sections of the substrate.

Sub
a4
1 26. The device of claim 18, wherein a minimum voltage needed to cause the substrate
2 to be conductive ranges between 10 volts and 300 volts.

1 27. The device of claim 18, wherein a minimum voltage needed to cause the substrate
2 to be conductive ranges between 30 volts and 100 volts.

1 28. The device of claim 18 wherein the surface of the substrate includes a vias
2 extending through the substrate, a current carrying layer being formed on a surface
3 defining the vias, the current carrying layer being formed by contacting the surface
4 defining the vias with a current carrying formation precursor while applying a voltage to
5 the substrate that is sufficient to cause the substrate to be conductive.

1 29. The device of claim 28, wherein the current carrying layer is formed on the surface
2 defining the vias during the process that forms the current carrying formation on the
3 substrate.

1 30. The device of claim 28, wherein the current carrying layer is formed on the surface
2 defining the vias during a process that includes using an electrode to plate the current
3 carrying formation on the selected sections of the substrate while a voltage is applied to
4 the substrate that is sufficient to cause the substrate to be conductive.

1 31. A device comprising:
2 a substrate comprising a voltage switchable dielectric material, the substrate having
3 a first surface and a second surface opposing the first surface, the substrate
4 including a vias that extends between a first surface and a second surface of the
5 substrate; and
6 a current carrying formation formed on a plurality of selected sections of the first
7 and second surfaces, and on a surface of the substrate defining the vias, the
8 current carrying formation being formed on the substrate by one or more
9 processes, each process including contacting the substrate with a current
10 carrying formation precursor while applying a voltage to the substrate that is
11 sufficient to cause the substrate to be conductive.

1 32. The device of claim 31, wherein a first current carrying formation on the first
2 surface and a second current carrying formation on the second surface of the substrate
3 each include a plurality of current carrying elements separated by a plurality of gaps, the
4 plurality of gaps on each of the first and second surfaces defining selected regions where a
5 corresponding non-conductive layer was formed.

1 33. The device of claim 32, wherein a first non-conductive layer was formed on the
2 first side of the substrate from a photo-imageable material that was imaged to define the
3 selected sections of the first surface of the substrate.

1 34. The device of claim 33, wherein a second non-conductive layer on the second side
2 of the substrate was formed from a photo-imageable material that was imaged to define
3 the selected sections of the second surface of the substrate.

1 35. The device of claim 34, wherein the first and/or second non-conductive layers were
2 each formed from a photoresist layer that was exposed with a mask, where the exposed
3 regions formed the selected regions of the respective first and/or second surfaces of the
4 substrate.

1 36. The device of claim 35, wherein the process includes using an electrode to plate
2 the current carrying formation on the selected sections of the first surface, second surface,
3 and/or surface of the substrate defining the vias.

1 37. A device comprising:
2 a first substrate comprising a voltage switchable dielectric material;
3 a first current carrying formation formed on a plurality of selected sections of a
4 surface of the first substrate, the first current carrying formation being formed
5 by a process that includes applying a first voltage to the first substrate that is
6 sufficient to cause the first substrate to be conductive;
7 a second substrate comprising a voltage switchable dielectric material, the second
8 substrate being adjacent to or stacked on the first substrate; and
9 a second current carrying formation formed on a plurality of selected sections of a
10 surface of the second substrate, the second current carrying formation being
11 formed by the process that includes applying a second voltage to the second
12 substrate that is sufficient to cause the second substrate to be conductive.

1 38. The device of claim 37, wherein one of the first or second substrates is positioned
2 to contact the surface of the other of the first or second substrates.

1 39. The device of claim 38, wherein the first substrate includes a vias within the first
2 substrate that accesses the surface of the second substrate, the current carrying formation
3 of the first substrate extending through the vias to extend electrical contact to the surface
4 of the second substrate.

1 40. The device of claim 37, further including a first non-conductive layer patterned
2 onto the first surface of the first substrate prior to the process to form the first current
3 carrying formation, a second non-conductive layer patterned onto the second surface of the
4 second substrate prior to the process to form the second current carrying formation, where
5 gaps in the first and second non-conductive layers define the plurality of selected sections
6 where the current carrying formation is subsequently formed on the respective first and
7 second surfaces.

1 41. The device of claim 40, wherein the first and/or second non-conductive layers are
2 formed from a photo-imageable material that is imaged to define the selected sections of
3 the respective first surface and/or second surface.

1 42. The device of claim 37, wherein one of the substrates comprises the voltage
2 switchable dielectric material formed from a first mixture, and another of the substrates
3 comprises the voltage switchable dielectric material formed from a second mixture that is
4 different than the first mixture.

1 43. The device of claim 42, wherein the first and second mixture each include a
2 binding agent, a conductive powder, and a cross-linking agent.

1 44. The device of claim 43, where the conductive powder of each of the first and
2 second mixtures includes an element selected from the group consisting of nickel,
3 aluminum, silver, copper, tin, and gold.

1 45. The device of claim 37, wherein the first current carrying formation is formed from
2 a material having a first composition, and the second current carrying formation is formed
3 from a material having a second composition different than the first composition.

1 46. The device of claim 45, wherein the first and second current carrying formations
2 are each formed from material selected from the group consisting of gold, silver, nickel,
3 tin, and aluminum.

1 47. The device of claim 37, wherein the first substrate is stacked over the second
2 substrate and a third substrate.

1 48. The device of claim 37, wherein the first substrate is placed in an end-to-end
2 orientation relative to the second substrate.

sub 95 1 49. A semiconductor device including a substrate upon which circuitry forming the
2 functionality of the semiconductor device is positioned, wherein the improvement
3 comprises:
4 the substrate comprising a voltage switchable dielectric material; and
5 a current carrying formation formed on a plurality of selected sections of a surface
6 of the substrate.

1 50. The semiconductor device of claim 45, wherein the semiconductor device includes
2 devices selected from a group consisting of integrated circuit devices, computer
3 processors, computer readable memory devices, motherboards, and PCB.